

FF20

FF 20 Floor Finishing *Liquid for damp insulation*

FF 20 (Floor Finishing) seals, protects and cures the surface of cement finished industrial floors. It is used as a final technological layer in order to protect the fresh surface from drying out.

SPECIAL PROPERTIES:

- easy to use
- does not contain silicon or any similar materials
- reduce crack probability
- milk white colour

FIELDS OF USE:

- Industrial floors
- Outdoor concrete slabs
- Indoor concrete slabs

METHOD OF USE:

Spray FF 20 on fresh concrete surface.

APPLICATION:

The typical way of useage is to apply it to the top of concrete surface. The area should be divided into adequate parts, where the specified quantity of the material should be used.

FF 20 should be applied in two coatings in the total quantity of 0.10 to 0.20 l/m².

The application should be made with a sprayer.

FF 20 provides a unified smooth finish.

COVERAGE / YIELD:

FF 20
5 to 10 m² / litre,
i.e. 0,10 to 0,20 litre / m² (one coat).

DRYING TIME:

The surface is touch dry after cca. 2 to 4 hours at 20°C.
Completely dry after cca. 24 hours at 20°C.

SHELF LIFE:

12 month from the dispatching date in unopened original containers.
Protect from frost and high temperatures.

PACKAGING:

FF 20 is supplied in 20 l, 60 l or 120 l cans.

„Minden, amit az ipari padlóról tudni kell...”

„You can bet on Betonmix!”