



TOPMIX®

TOPMIX® Floor surface hardener

TOPMIX® is a pre-blended cementitious powder mixture, containing selected nonmetallic aggregates, special cements and compatible admixtures.

TOPMIX® is used to create durable topping of monolithic concrete floors. Use immediately after pouring concrete slab.

TOPMIX® to be sprinkled on the fresh wet concrete. Repeated power trowelling forms durable, smooth and non-slip surface.

TOPMIX® topping provides increased **resistance against** oil and grease penetration. Industrial floors with **TOPMIX®** dry shake topping are extensively used in warehouses, factories, working areas, shopping centres etc. and generally everywhere, where durable and abrasion resistant surface is required.

SPECIAL PROPERTIES:

- Resistance to medium duty
- Dust free
- Cost effective
- Guaranteed quality – no site production

TECHNICAL DATA:

- Compressive strength: ≥ 80 N/mm²
MSZ EN 13892-2:2003 Class: C80
- Abrasion resistance: $\leq 6,0$ cm³ / 50 cm²
MSZ EN 13892-2:2003 Class: A6
- Bending-tensile strength: $\geq 7,0$ N/mm²
MSZ EN 13892-2:2003 Class: F7
- Temperature for use: 5 °C-30°C

SHELF LIFE:

12 month from the dispatching date in original unopened packs. Protect from frost and wet conditions.

SAFETY AND HEALTH PROTECTION:

The product contains cement, therefore it is necessary to wear protective gloves and goggles.

PACKAGING:

TOPMIX® is supplied in 30 kg bags or in 40 bags on a pallet, total weight of 1.200 kg.

TOPMIX® is supplied in natural gray colour. Possible other colours to be consulted.